



# DEEP CYCLE AGM TECHNOLOGY

## LDC6-350 BCI GROUP 902

### FEATURES & BENEFITS

- True deep cycle AGM technology-GREEN SOLUTION
- Over 99.99% virgin lead for grid plate and active material
- Heavy duty grid/paste design for deep cycle application
- Maintenance free, non-spillable, valve-regulated
- Double separator configuration: long cycle life & High energy density and super anti-vibration design
- Low self-discharge for longer shelf life



### ELECTRICAL SPECIFICATIONS

Voltage(V)	Capacity (AH)					Reserve Capacity (Min)		
	100HR	20HR	10HR	5HR	3HR	@25A	@56A	@75A
6	385	350	332	305	285	820	/	240


### PHYSICAL SPECIFICATIONS

Model	Dimensions (mm/inches)				Weight (kg/lbs)	Terminal Type (Standard)	Case Material
	Length	Width	Height	Total Height			
LDC6-350	295 (11.61)	180 (7.09)	346 (13.62)	368 (14.49)	48.2 (106.3)	DT-3/8	PP

Operating Temperature Range		
Discharge	Charge	Storage
-15°C ~ 50°C (5°F ~ 122°F)	0°C ~ 40°C (32°F ~ 104°F)	-15°C ~ 40°C (5°F ~ 104°F)

# LDC6-350


## DIMENSIONS




Note: D:Positive  $19.5_{-0.3}^0$ , D:Negative  $17.9_{-0.3}^0$ ; Terminal Torque Values in-Ib(Nm) :176-203(20-23)

## PERFORMANCE CHARACTERISTICS


### LEOCH LDC AGM Charging Profile




### Relationship of OCV and State Of Charge ( $25^\circ C, 77^\circ F$ )



### Cycle life in relation to Depth Of Discharge



### Self-discharge Characteristic



- LEOCH INTERNATIONAL SALES OFFICE:  
Add: 5th Floor, Xinbaohui Bldg.  
Nanhai Blvd, Nanshan, Shenzhen, China. 518054  
Tel: +86-755-86036060(100 lines) Fax: +86-755-26067269  
E-mail: export@leoch.com  
web: www.leoch.com