

ODYSSEY Extreme Series Battery

ODX-AGM31

(31-PC2150S)

(Group 31 with SS 3/8 inch threaded stud terminals and single external vent)

Today's commercial vehicles have to power a range of accessories, both inside the cab and out. And whether on the road, the farm, or the jobsite, ODYSSEY batteries have the power to start any job, and the durability to last until it's finished.)

Featuring rugged construction and packed tightly with pure lead plates, the non-spillable AGM design ODYSSEY battery protects against the shock and vibration that can quickly destroy other batteries. And the pure lead plates mean 2 times the overall power and 3 times the life of conventional batteries, up to 400 cycles at 80% depth of discharge!

Bottom line? ODYSSEY batteries deliver massive starting power, rapid recovery, and extreme durability that heavy duty and commercial vehicles demand.



Dimensions

Length	13.00 in
Width	6.80 in
Height (terminals included)	9.49 in
Height (container)	8.49 in
Weight	77.80 lbs

Specifications

Voltage	12
Pulse (5 second) Hot Cranking Amps (PHCA)	2150
Cold Cranking Amps (CCA)	1150
HCA	1545
MCA	1370
20Hr Nominal Capacity (Ah)	100
10Hr Nominal Capacity (Ah)	92
Reserve Capacity Minutes	205
Terminal	3/8-16" Stud
Torque Spec in-lbs (Nm max)	200 (22.6) Studs only
Internal Resistance	2.2
Short Circuit	5000